TECHNICAL DATA FOR INTERLOCKING PAVING TILES
Vario Quadro

Made to BS 6717: Part 1: 1993.

Average compressive strength : ≥52 N/mm²

Minimum compressive strength : ≥47 N/mm²

Average limit of water absorption : ≤4.0 % by mass

Water cement ratio : 0.4

Interlocking Tiles : Products Technical Data-
Vario Quadro

Product Name	Height (cm)	No of Blocks in One Pallet (pieces)	Area of One Pallet (m2)	No of Blocks in One m2 (pieces)	No of Blocks in One Bundle (pieces)	Area of One Bundle (m2)	Weight c (Kg)
Cube 8x8	6	156	1.000	156	1560	10	0.9 Kg
Cube 8x8	8	130	0.832	156	1040	6.656	1.2 Kg
X-Shape	6	48	0.922	52.05	480	9.22	2.7 Kg
X-Shape	8	48	0.922	52.05	384	7.376	3.6 Kg
Rhombus (Vario)	6	56	0.924	60.61	560	9.24	2.3 Kg
Rhombus (Vario)	8	56	0.924	60.61	448	7.392	3.1 Kg
Octagonal	6	30	1.008	29.76	300	10.08	4.7 Kg
Octagonal	8	30	1.008	29.76	240	8.064	6.3 Kg